

# ING- 08

**Gas-filled tube based  
pulsed neutron generator  
for logging equipment**

## ➔ THE GENERATOR DESIGN INCLUDES:

- neutron emission unit;
- power supply and control unit.

Both units are housed in the metal cylinders.

Electric power is supplied to the generators from 200 V DC source, and control is exercised either by supplying positive polarity voltage (5 V) or via the built-in RS232 standard serial interface.

## ➔ ING-08 TECHNICAL CHARACTERISTICS:

Neutron flux, neutron/sec .....	$5 \times 10^7$
Neutron pulse width, $\mu\text{sec}$ .....	20-100
Frequency, Hz .....	400-10000
Operating life time, h .....	300
Power consumption, W .....	not more than 30
Neutron emission unit dimensions	
Diameter, mm .....	34
Length, mm .....	1820
Maximum operating temperature, $^{\circ}\text{C}$ .....	+120

Russian Federal Atomic Energy Agency



**ALL-RUSSIA RESEARCH  
INSTITUTE OF AUTOMATICS**

**For Express Mail:**

22, ul. Sushchevskaya, Moscow, Russia

**Phone:** (499) 978-7803

**Fax:** (499) 978-0903

**E-mail:** [vnii@vniia.ru](mailto:vnii@vniia.ru)

**http://www.vniia.ru**